



MODEL : SETU 32'	MODEL : SETU 20'
Professional Motorized system for smooth & Dynamic Shots	Professional Motorized system for smooth & Dynamic Shots
Fully Battery operated & 240V power operated	Fully Battery operated & 240V power operated
Payload Capacity : 40 Kg	Payload Capacity : 25 Kg
45 Degree Tilt & 360 Degree pan movement	45 Degree Tilt & 360 Degree pan movement
Stabilized Telescopic arm motion	Stabilized Telescopic arm motion
Electric touchscreen control	Electric touchscreen control
Programmable telescopic arm Range & speed	Programmable telescopic arm Range & speed
Telescopic Arm weight without payload : ~250 Kg	Telescopic Arm weight without payload : ~100 Kg
Total weight with Dolly & all counter weight : ~1100 Kg	Total weight with Dolly & all counter weight : ~600 Kg
Telescopic Arm speed 1.5 m/s per second	Telescopic Arm speed 1 m/s per second
Telescopic range : 20' Feet	Telescopic range : 15' Feet
Fully Extended length 32' Feet	Fully Extended length 20' Feet
Smooth and silent movement	Smooth and silent movement
Motion control & Encoding (Tilt & Pan)	Motion control & Encoding (Tilt & Pan)
Quick Setup & Easy to transport	Quick Setup & Easy to transport
Hydraulic Fluid head	Hydraulic Fluid head
Cost Effective	Cost Effective
Heavy duty construction from Aerospace grade Alluminum & Stainless steel Alloy	